## **Perfectly Green Product Information**

**Product: Bespoke Design Product – Fibrillated** 



Туре:	Polyethylene Fibrillated	Standard colours availab
Dtex:	8.800/11.000	
T. 6. Ch		F1 - white
Tuft Characteristi		
Pile Height:	15 - 60 mm (margin +/- 5%)	F11 - grey
Stitch Rate:	150 - 220	
Gauge:	5/16" 3/8"	F2 - black
Tuft Lock:	2 kg	
Backing Characte	eristics	F22 - vegas gold
Primary Backing:	Woven Polyester	Ec. halabasella
Secondary Backing:	Latex	F6 - bright yello
Water permeability:	drainage holes on request	F2
Total Product We	ight	F3 - straw yellov
	on pile height and stitch rate	F4 - orange
Warranty		F7 - clear red
	liscoloration and UV light degradation.	
2 year product warranty	against fibers coming off.	F5 - red clay
Logo/Design		F22 maraon
	ur logo or design, a Vector file is required. With preference .eps or .ai file.	F23 - maroon
Besides a square or recta	ngle mat, we can also tuft the shape of a logo or design like a circle, ellipse,	F13 - bright blu
hexagon or crest.		F13 - bright blu
Margin total size logo ma	at: +/- 5%	F8 - reflex blue
Guidelines Logo/	Design	TO TELEX DIGE
	need to be legible and feasible, so please take following guidelines in account:	F21 - lime greer
Product:	Fibri 24 mm (5/16"gauge)	
Minimum height letter:	8 - 10 cm	F9 - olive green
Detail (width):	1.0 cm	
Space in between letters		F10 - field green
		Otherseless
Possibilities		Other colours on regulaci
Possibilities It's possible to supply us	with your own yarn, under the condition a production test is permitted.	Other colours on request.

The maximum size out of one piece is 9x4 meters. Larger size logo mats will consist out of multiple parts of

which the joints need to be glued on location.