

Perfectly Green Product Specification Sheet



Product: Tough Colours 10mm

Walkways, Paths, Exhibitions, Events, High Footfall Areas



10mm Pile Height



Latex backing, pre-punched for drainage



DIN 53387 Standard (6000 hours)



No sand infill required



Available in 2m Width



Available in 4m Width

Perfectly Green, Ridgewood Industrial Estate,
Uckfield, East Sussex, TN22 5QE
All information correct at time of printing

Technical Specification

Product application: Walkways, Paths, Exhibitions, Events, High Footfall Areas

Material: Polypropylene (UV stabilised)

Yarn Type: 5,000/8 dTex monofilament curled

Yarn Quality: Environmentally friendly, free of Lead & Cadmium

Pile height: 10mm with 5/32 gauge

Production method (DIN61151): Tufted

Stitches for 10 cm +/-1: 32

Stitches for m2 approx: 80,640

Total weight gr/m2 +/-10%: 1,826 gr/ m2

Composition: PE Monofilament curled

Blade Type: Curled

Colours: Red, Blue, Yellow, White, Black & Green

Colour Fastness: Xenon test Blue scale > 7, Grey scale > 5

Primary backing: 100 % Polypropylene 146 gr/m2

Backing: Latex 836 gr/m2

UV stability: DIN 53387 Standard (6000 hours)

Water permeability: 60 litre/min

Installation method: Please see our website www.perfectlygreen.co.uk for the installation manual

Applications Play, Multi Use Games Areas, Gardens, Landscaping, Terraces, Indoor, Events, Exhibitions

Contact us for more information:

01825 729259

sales@perfectlygreen.co.uk

www.perfectlygreen.co.uk

