

# Perfectly Green Product Information



## 310 ml Glue Tubes

### Technical Data

#### Special features

- High adhesive strength
- Waterproof
- Good stability
- Rapid hardening
- Very high initial adhesive strength

**Suitable for installation** - Synthetic turf  
Sports floor coverings  
Elastic strips

**Suitable subfloors** - Concrete (easy-grip surface)  
Asphalt  
Screeds

**Suitable underlays** - Seaming tape C 145  
Seaming tape C 345  
Seaming tape P 145  
Seaming tape C 140  
Seaming tape C 230  
Seaming tape C 166

**Product properties** - Easy to apply  
Heat- and cold-resistant

**Colour** - Green

**Quantities per m<sup>2</sup>** - Required quantities per m<sup>2</sup>: depending on substrate

**Open time** - 5 - 15 minutes at 20 °C

**Accessibility** - After 24 - 48 hours

**Climate at work site** - Minimum 15 °C, maximum 75% rel. humidity, preferably max. 65%

**Transport requirements** - Frost-free

**Storage requirements** - Frost-free

**Shelf-life** - 6 months

**Available packaging** - 310 ml plastic cartridge

**Giscode** - RU1



**PROCESSING**

Adhesion areas must be stable, dry and free of dust and grease. Depending on the material the adhesive must be applied across the entire area or joining tape width. Apply part to be glued, correct position as necessary and press down firmly. Fix for 12 hours if necessary. Remove fresh adhesive residue immediately. Hardened adhesive can only be removed mechanically.

**OTHER INFORMATION**

The adhesive will harden through reaction with moisture. The speed of hardening is increased by a higher environmental temperature. Considering the many possible materials and substrates it may be necessary to carry out your own test before bonding.