Perfectly Green Product Specification Sheet

Product: Perfectly Green Glue for Artificial Grass joins



Product number	✓ 127170
Special features	 High adhesive strength Waterproof Good stability rapid hardening very high initial adhesive strength
Suitable for installation of	 Synthetic turf sports floor coverings elastic strips
Suitable subfloors	 STAUF levelling compounds concrete (easy-grip surface) asphalt screeds
Suitable underlays	 Seaming tape C 145 Seaming tape C 345 Seaming tape P 145 Seaming tape C 140 Seaming tape C 230 Seaming tape C 166
product properties	easy to applyheat- and cold-resistant
Color	✓ green
Required quantities per m²	✓ Required quantities per m²: depending on substrate
Open time	✓ 5 - 15 minutes at 20 °C
Accessibility	✓ after 24 - 48 hours
Room climate at work site	minimum 15 °C, maximum 75% rel. humidity, preferably max. 65%
Transport requirements	✓ frost-free
Storage requirements	✓ frost-free
Shelf-life	✓ 6 months
Available packaging	✓ 310 ml plastic cartridge
Giscode	✓ RU1



PROCESSING

Adhesion areas must be stable, dry and free of dust and grease. Depending on the material the adhesive must be applied in spots, lines or across the entire area. Apply part to be glued, correct position as necessary and press down firmly. Fix for 12 hours if necessary. Remove fresh adhesive residue immediately. Hardened adhesive can only be removed mechanically.



OTHER INFORMATION

The adhesive will harden through reaction with moisture. The speed of hardening is increased by a higher environmental temperature. Considering the many possible materials and substrates it may be necessary to carry out your own test before bonding.



LIMITATION OF LIABILITY

The foregoing representations are based on the results of our most current product and material testing and are of a non-obligatory advisory nature only since we have no control over the actual quality of workmanship, materials used and worksite conditions. As such, they do not constitute an express or implied warranty of any kind. The same applies to our commercial and technical consultation services which are provided free-of-charge and without obligation. Therefore, we strongly recommend that prior onsite testing be conducted to observe and study the suitability of the product for the intended purpose. With the release of this technical information, all prior technical information (technical data sheets, installation recommendations and other information regarding similar purposes) becomes invalid.

Perfectly Green, Ridgewood Industrial Estate, Uckfield, East Sussex, TN22 5QE All information correct at time of printing

Contact us for more information:

01825 729259

sales@perfectlygreen.co.uk
www.perfectlygreen.co.uk



