

# Perfectly Green Product Specification Sheet

Product: Shock Pads 25mm, 35mm and 45mm  
Play Areas



Perfectly Green, Ridgewood Industrial Estate,  
Uckfield, East Sussex, TN22 5QE  
*All information correct at time of printing*

## Technical Specification

**Product application:** Play Areas

**Pad depth:** 25mm, 35mm, 45mm or a combination to also give 60mm and 80mm

Lower layer shock pad system made of agglomerated and regenerated polyethylene.

High Permeability

**Example Critical Fall Height Information:**

**Perfectly Green Corvette 30mm pile height**

Pad Depth	Critical Fall Height
25mm pad	1.2m
35mm pad	1.7m
45mm pad	1.9m
60mm pad (25+35)	2.2m
80mm pad (35+45)	2.5m

**Each pad dimension:**

**0.9m x 2.25m covering 2.025 sqm – straight edges**

Pad weight:	Tensile Strength:	Density:
<b>25mm</b> – 4kg	0.18 Mpa	80 kg/m <sup>3</sup>
<b>35mm</b> – 6kg	0.24 Mpa	80 kg/m <sup>3</sup>
<b>45mm</b> – 8kg	0.38 Mpa	80 kg/m <sup>3</sup>
<b>60mm</b> – 10kg		
<b>80mm</b> – 14kg		

If supplied in 'jigsaw' format the pads will fit together. If supplied in straight edge format please use tape to join them together.

**Contact us for more information:**

01825 729259

[sales@perfectlygreen.co.uk](mailto:sales@perfectlygreen.co.uk)

[www.perfectlygreen.co.uk](http://www.perfectlygreen.co.uk)

